

the transportation means, especially side tarpaulins of a truck. Thus, with such systems, unauthorized access to the cargo space can take place without this being detected by such a monitoring system. On the other hand, the use of monitoring cameras has the drawback that they can be relatively sensitive to impact and weather conditions, especially in conjunction with the image-recording systems, and consequently are only somewhat suitable for sturdy long-term use, also under adverse ambient conditions. Moreover, the recording and archiving of the image data in the form of magnetic storage media such as video cassettes makes it more difficult to systematically evaluate the image material since fairly irrelevant information and hence fairly large volumes of information are stored in the process.

SUMMARY OF THE INVENTION

[0005] In order to secure valuable goods, complex and thus costly procedures can be necessary in which, for example, barcodes or transponder security systems for goods are used or else specially trained personnel conduct random inspections or even physically accompany the goods.

[0006] An object of the present invention is to provide a monitoring system for the cargo space of a transportation means that, on the one hand, has a sturdy design and is thus especially well-suited for reliable use, even under adverse ambient conditions and that, on the other hand, ensures high reliability in terms of monitoring the cargo space. Moreover, a method that is especially suitable for monitoring the cargo space of a transportation means is to be put forward.

[0007] with the present invention provides a control unit that can receive a characteristic value for the current state of motion of the transportation means, and that is connected to a number of motion detectors on the data input side and to a number of image-recording devices on the data output side.

[0008] An especially high level of security and reliability can be achieved with actual cargo space monitoring using optical monitoring means, especially image-

for the monitoring system to be activated – for instance, manually – when the transportation means is standing still or when another situation is present that might be theft-relevant. This can especially be the case if the transportation means is a container, particularly a shipping container.

[0011] The motion detector can be, for example, commercially available motion detectors that can ascertain especially human movements in the cargo space. As an alternative or additionally, the motion detectors advantageously comprise a number of acceleration sensors that can supply acceleration data for the cargo space particularly in three dimensions and direction-dependently. Such acceleration sensors can be configured to be so sensitive that, for example, the vibrations and position changes on the load surface generated by movements of persons on the load surface of a truck can be registered. In an especially advantageous embodiment, such acceleration sensors can also be used to ascertain a shift of the goods during transportation so that, in such a constellation, the monitoring system can be used to monitor the goods in terms of damage during transportation, for example, due to extreme vibration, shock stress and the like.

[0012] In order to allow a data transfer and/or a later external evaluation of the recorded image data, the image-recording device or each image-recording device is advantageously connected to a memory module. In an especially advantageous embodiment, the memory module in question is configured for digital data storage, preferably a configuration as a multi-media card being provided. These can be especially digital memory cards such as those that can also be used, for instance, in digital cameras. On the one hand, such memory cards can be used within a relatively wide temperature range from -25°C to +85°C [-13°F to 185°F] so that a reliable operation of the monitoring system including the storage of the recorded image data is possible, even under relatively adverse ambient conditions. Moreover, such memory cards are particularly resistant to the shock and vibration stresses that occur within the scope of the operation of trucks. Furthermore, they are largely maintenance-free and stand out for their small space requirements as well as relatively low production or purchase costs. It is precisely the demand-driven recording of monitoring images achieved with the monitoring system that

leads to a marked reduction in the requisite storage capacities, so that the advantages of such memory cards can be utilized without the drawback that the storage capacity would be too small for purposes of recording.

[0013] Advantageously, characteristic values for authorized loading and/or unloading positions are stored in the memory module of the monitoring system. In this manner, an additional criterion that can be taken into account is the demand-driven activation of the monitoring system in order to determine whether the transportation means is currently in a position in which loading and/or unloading procedures can be expected, so that here, no activation is necessary, even if a movement is ascertained.

[0014] A very suitable demand-driven utilization of existing storage capacities and a very systematic concentration of the image recording on situations truly considered to be relevant can be achieved in that, after having been activated by the control unit, the image-recording device or each image-recording device advantageously records a predefinable number of images, after which the image-recording device in question is once again deactivated. Thus, the control unit starts the image recording once a relevant situation has been recognized on the basis of the determined input data, for example, due to movement on the load surface. However, after the image recording has started, it does not continue indefinitely but rather is limited to a predefinable data volume. Here, for example, a predefined period of observation or else a predefined number of individual images to be recorded can be specified as the limit for the image recording. Once this limit has been reached, the image-recording device in question is deactivated, a process in which it can deactivate itself autonomously or else it can be deactivated by the central control unit.

[0015] The fundamental configuration of the monitoring system allows a very compact and as-needed archiving of relevant image data that facilitates, among other things, a later evaluation of the data material received. Moreover, in order to contribute to protecting the goods against theft, also in the sense of providing active security measures, an especially advantageous embodiment of the monitoring system is equipped with

means for systematically triggering an alarm if a theft attempt is detected. Using the configuration of the monitoring system for systematically initiating certain measures after the detection of a theft attempt, for example, on the basis of the motion detector, this information can be used not only to trigger the demand-driven image recording but also to generate alarm messages and the like. For this purpose, the control unit of the monitoring system is advantageously connected on the data output side to a transmitter for wireless data transmission via which, for example, alarm messages can be sent if necessary. In particular, a cellular module can be provided (GSM module or, for example, satellite-aided via INMAR-SAT), with which, for example, a message can be sent to a cellular telephone of the driver or to a central station if movement on the load surface is detected.

[0016] In another advantageous embodiment, the monitoring system is equipped with a GPS (Global Positioning System) unit so that additionally, data can be provided about the current position of the transportation means, for example, the truck. This position information can be stored together with the recorded image data so that – optionally with the additional storage of the date and time – a precise spatial association can be made with the recorded image data. Furthermore, however, the position data can also be transmitted together with the alarm message or with other data to external recipients such as, for instance, a central station, so as to allow a real-time tracking of the occurrences taking place on the load surface and, at the same time, a determination of the position. Moreover, as a result, an external unit such as, for example, a logistics center, can at any time request the position and the operating status of the transportation means and can externally trigger the transmission of images. Especially advantageously, the data thus acquired can be used in combination with characteristic values stored in the memory unit pertaining to positions where loading and/or unloading procedures are scheduled and where movements in the transportation means are to be expected anyway.

[0017] Advantageously, the control unit of the monitoring system is connected on the data input side with an information system on the transportation means. In the case of a truck, this can especially be an information system about the current driving status such

as, for example, a speedometer. Thus, in an especially simple manner, the current state of motion of the vehicle can be ascertained and the information pertaining to this can be further processed appropriately. In particular, it can be provided that the image-recording devices or other measures are only activated when no driving speed is registered, that is to say, when the vehicle is at a standstill, in which case theft would actually be conceivable. As an alternative or additionally, the control unit can also be connected to the ignition lock on the truck so that alarm or detection procedures are only initiated if the ignition lock has not been actuated and consequently the driver is not in the vehicle.

[0018] In order to even further expand the functionality of the monitoring system, in another advantageous embodiment, the control unit is fitted with a number of interfaces that, as needed, serve to connect other functional components such as, for example, barcode scanners or article security systems. The information that can be obtained in this manner can also be stored electronically or digitally. Thus, in particular, goods identification systems for systematically tracking the goods can be installed, for example, during loading or unloading.

[0019] The monitoring system is suitable for use in different kinds of transportation means in which theft of the goods might have to be considered as a possibility such as, for example, airplanes, shipping containers or other containers and the like. In an especially advantageous embodiment, however, the monitoring system is configured for use in trucks.

[0020] The present invention also provides a method in which a number of image-recording devices are activated as a function of the current state of motion of the transportation means and of movement ascertained in the cargo space. This ensures that images are only recorded in situations that have been recognized as being relevant, so that the data processing and archiving are kept especially simple.

[0021] Advantageously, the movement in the cargo space is ascertained on the basis of acceleration data about the transportation means. Here, in particular, acceleration

mode”, can save considerable power and resources. Only when needed, that is to say, when unauthorized movement is detected on the load surface, is the system fully activated, which then calls for correspondingly greater power consumption.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] An embodiment of the invention is explained in greater detail with reference to a drawing, in which the following is shown:

[0027] Figure 1 a schematic depiction of a monitoring system, and

[0028] Figure 2 a truck equipped with a monitoring system according to Figure 1. The same parts are designated with the same reference numerals in the figures.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

[0029] The monitoring system 1 according to Figure 1 is intended to secure the cargo space of a transportation means against theft of the goods held there. The transportation means can be especially a truck, an airplane or a container such as, for example, a shipping container, whereby the monitoring system 1 is also suitable for use in other transportation means where, for example, theft is a concern because of the valuable goods being transported. The monitoring system 1 is configured essentially for an optical monitoring of the cargo space and comprises a number of image-recording devices 2 that can be configured especially as rapid video cameras. The image-recording devices 2 can create an optical documentation of events on the cargo space that is to be monitored, so that persons and the like can be subsequently identified on the basis of the data acquired in this manner for a later evaluation.

[0030] The monitoring system 1 is configured for high operational reliability, along with an especially low need for storage capacity for the optical information obtained. For this purpose, it is provided that the image-recording devices 2 of the monitoring system 1 do not continuously record image data in the active mode but rather, that the image data recording is triggered on-demand only when this is considered necessary. To this end, the

[0033] In order to be able to suitably provide the recorded image data for purposes of later evaluation or archiving, the image-recording devices 2 and the control unit 4 are connected to a memory unit 12 comprising a memory module 14 that is suitable for digital data storage such as those that can also be used in digital cameras. This memory card can be removed from the memory unit 12 and can be further processed in other suitable peripheral devices such as a personal computer, whereby, for example, a data transfer for archiving or else a digital image enlargement and the like can be performed. In order to prevent manipulation, the recordings are suitably coded in the memory module 14 so that an accurate evaluation is ensured. Moreover, the information on the memory module can be compressed by means of an appropriate method such as JPEG 2000 in order to keep the required storage capacity especially small.

[0034] In addition, the control unit 4 is also equipped with an interface 16 for connecting external sensors and with another interface 18 for connecting other functional units such as a transmitter for wireless data transfer, a GPS receiver and the like.

[0035] The control unit 4, the memory unit 12 and the image-recording devices 2, via the associated multiplexer 6, are also connected to a shared power supply 20 which, in turn, is connected on the input side to the power supply of the transportation means, especially the on-board electronics of a vehicle. The control unit 4, the multiplexer 6, the acceleration sensors 8 and the memory unit 12 are arranged inside a shared housing 22. Since the essential functional components can be configured using integrated chip technology, the outer dimensions of the housing 22 can be kept relatively compact.

[0036] As can be seen in Figure 2, the monitoring system 1 can be integrated especially into a truck 30 and can serve to monitor its cargo space 32. The image-recording devices 2 are mounted inside the cargo space in a suitable manner, especially on one end, so that complete spatial monitoring of the interior of the cargo space 32 is possible. The control unit 4 is connected on the input side to the on-board electronics 34 of the truck 30 so that especially the speedometer pulse and/or information as to whether the ignition is switched on can also be taken into account when the information is being

processed. Moreover, the control unit 4 in the embodiment according to Figure 2 is connected to additional sensors 36 that, on the one hand, can provide additional information about the current state of motion of the cargo space 32 but, on the other hand, can also supply additional information about the ambient pressure, ambient temperature and the like that allow a readjustment of measured values acquired elsewhere. Furthermore, in the embodiment according to Figure 2, the control unit 4 is connected to an antenna system 38 for GPS and cellular telephony.

[0037] The monitoring system 1 is essentially intended to ascertain by means of the acceleration sensors 8 or other motion detectors whether there are movements of the cargo space 32 or in the cargo space 32 when the transportation means in question, especially the truck 30, is at a standstill. If such a relevant movement is recognized, for example, through shock and/or vibration, the image-recording devices 2 are activated by the control unit 4. After their activation, the image-recording devices 2 record a predefinable number of images and are subsequently once again deactivated. As a result, the recorded images and the data that was also recorded are reduced to an especially small data volume, a process in which it is also ensured that only relevant data is forwarded for purposes of further evaluation. In this manner, with high security, an especially small storage requirement is ensured.

[0038] As soon as the movements on the load surface 32 that have been ascertained as being relevant allow the conclusion that loading, unloading (either authorized or unauthorized due to theft) or else damage or destruction of the goods have taken place, a predefined number of images are recorded by the image-recording devices 2, which are subsequently stored on the memory module 14 in digital form. This procedure can also be triggered by external sensors such as, for example, by infrared motion detectors, door contacts and the like. The date and time of the event are automatically superimposed onto and stored along with the stored images so that a subsequent evaluation and allocation of the recorded data are greatly simplified.

selected components ensure good resistance to temperature and a wide operating range of possible ambient temperatures from -25°C to $+85^{\circ}\text{C}$ [-13°F to 185°F]. Moreover, the monitoring system 1 is not sensitive to vibration or shock stresses, and in addition, any manipulation of the recorded images is ruled out.

[0042] As an alternative, the monitoring system 1 can also be configured for monitoring a container such as, for example, a shipping container. Here, it is especially taken into account that such applications can entail a relatively long period of time during which the system is disconnected from the power source so that a low power consumption of the monitoring system is of special importance. For such an application, the functional components of the monitoring system are advantageously arranged in a housing 22 that is sealed against ocean water or salt water.